

QUALITY MANAGEMENT ISO 9001 TD_EGGER_Silenzio_Easy_EN Code:

Revision:

Date: 18.11.2020



EGGER Silenzio Easy

Application area
Underlay material for floating flooring installation of laminate flooring elements (EN 13329)



Product	Silenzio Easy	
Material	HFPS-Foam	
Color	green	
Type of delivery	Folding panel	
Packaging	15 m² / package	21 packages / pallet
Accreditations /Certificates /Declarations	Building Inspectorate Approval TÜV toxproof, A-intérieur)	- (Émissionsdans l'air

Material data

Parameter	Specification	Tolerance	Test method	
Thickness [mm]	2	± 15%	CEN TS 16354	
Length [m]	12	+5% / -0%	CEN TS 16354	
Width [m]	1.25	+2.5% / -1%	CEN TS 16354	
Reaction to fire	EfI	-	EN 13501	
Thermoforming [°C]	≤ 70	-	S WN	
Water absorption [%]	≤1	-	EN 12087	
Thermal resistance Rλ [m²K/W]	~ 0,057	-	EN 12667	
Water vapor diffusion resistance SD [m]	-	-	CEN TS 16354	

Technical data concerning CENTS 16354

Description	Parameter	Value	Recommendations according to the EPLF
Impact Sound Reduction	IS [dB]	≤ 18	≥ 18
Reflected Walking Sound Reduction	RWS	up to 37 % according to IHD W431	in progress
Resistance to Large Ball	RLB [mm]	≥ 1400	≥ 1200
Compressive Strength	CS [kPa]	≥ 110	≥ 60
Compressive Creep	CC [kPa]	≥ 30	≥ 20
Dynamic Load	DL [cycles]	≥ 250000	≥ 100000
Punctual Conformability	PC [mm]	≤ 1.3	≥ 0.5

MORE FROM WOOD.



Information: All above mentioned values were determined under laboratory conditions and defined laboratory materials and structures and may with different system flooring components deviate from these test values. For all of they mentioned performance values inaccuracies are possible owing to the testing methods.

The information given above is based on our current state of know ledge and should be used for information of our product application. This should not be taken to as an assurance of certain quality of our products or their use for specific purposes. Subject to change, legal obligations cannot be derived from the information in this document. Existing commercial protective rights are to be observed.